



STANDARD CONSTRUCTION NOTES FOR STREET NAME SIGNS

1. ALL STREET SIGNS SHALL BE 3M DIAMOND GRADE DG3 DOUBLE-FACED EXTRUDED BLADES.
2. FIRST LETTER OF SUFFIX SHALL BE UPPERCASE WITH ALL REMAINING LETTERS TO BE LOWERCASE
3. ADDRESS NUMBERS FOR STREET NAME BLADES WILL BE PROVIDED AT A LATER DATE.
4. STREET SIGN POSTS SHALL BE 12 FEET LONG, 4 FEET DRIVEN INTO THE GROUND.
5. SIGN POSTS FOR STREET NAME BLADES SHALL BE ROUND TUBULAR ALUMINUM OR HOT DIPPED GALVANIZED STEEL, OUTSIDE DIAMETER 2-3/8 INCHES, WALL THICKNESS 0.109 INCHES.
6. ALL PUBLIC STREET NAME BLADES SHALL BE "GREEN" IN COLOR. LETTERING ON ALL STREET NAME BLADES SHALL BE HIGH INTENSITY, "WHITE" IN COLOR.



STANDARD DETAILS  
 STREET NAME BLADE SIGNS  
 PRIVATE STREETS  
 COTTAGE GROVE, MINNESOTA

JANUARY 2021

PLATE NO.  
 STR-30