



- | | |
|---|---|
| <ol style="list-style-type: none"> 1. PLASTIC VALVE BOX AND LOCKING COVER W/ BOX EXTENSIONS AS REQUIRED. REFER TO SPECS. HEAT BRAND 'GV' ON LID. 2. GATE VALVE W/ OPERATING NUT, SEE IRRIGATION LEGEND FOR MANUFACTURER AND MODEL NUMBER. 3. FINISH GRADE BEFORE PLANTING. 4. STD. BRICK, TYP. 2 PLACES. 5. 6" PVC SLEEVE. 6. SCH. 80 PVC FLANGES, TYP. 2 PLACES. | <ol style="list-style-type: none"> 7. KEEP FINISH GRADE BELOW VALVE BOX LID:
1½" IN SOD.
3" IN PLANTER BED. 8. INSTALL GATE VALVES A MIN. OF 24" FROM STRUCTURES OR HARDSCAPING. 9. INSTALL GATE VALVES IN PLANTING BEDS WHEREVER POSSIBLE. 10. INSTALL VALVE BOX SO THAT TOP OF VALVE BOX IS FLUSH W/ ADJACENT HARDSCAPING. 11. REFER TO SPECS. AND PLAN SHEETS FOR MORE INFORMATION. |
|---|---|



STANDARD DETAILS

GATE VALVE

COTTAGE GROVE, MINNESOTA

JANUARY 2021

PLATE NO.
IRR-3