



SECTION

- | | |
|---|---|
| <ol style="list-style-type: none"> 1. REMOTE CONTROL VALVE. 2. PLASTIC VALVE BOX WITH BOLT DOWN LID. HEAT BRAND VALVE NUMBER ON LID. 3. FINISH GRADE: HOLD 2" BELOW LID IN PLANTER AREAS. 4. UL LISTED WATERPROOF CONNECTORS. 5. STAMPED VALVE NUMBER TAG. 6. COILS: LEAVE EXCESS 2'-0" COILS IN EACH VALVE BOX. WRAP WIRE AROUND 1/2" PIPE 15 TIMES TO CREATE COILS. | <ol style="list-style-type: none"> 7. PVC SCHEDULE 40 ELL. 8. PVC SCHEDULE 80 NIPPLE (LENGTH AS REQUIRED). 9. 3" LAYER OF PEA GRAVEL. 10. BALL VALVE. 11. PVC MAIN LINE. 12. DRIP FILTER. 13. PVC UNION. 14. PVC LATERAL TO DRIP ZONE. 15. ALL WIRE TO BE INSTALLED AS PER LOCAL CODE. |
|---|---|



STANDARD DETAILS

DRIP REMOTE CONTROL VALVE

COTTAGE GROVE, MINNESOTA

JANUARY 2021

PLATE NO.
IRR-6